




Released

\*\*Confirm Revision Level Prior to Use\*\*

ALL FEMALE BULLET CONNS TO BE GREASED

1/4" RG TERM SMOOTH BORE SOLDER CRIMP AND H.S.

- (F1) ← (000) 14 WHT/BLK (1) GROUND
- ← (001) 16 BRN (2) TAIL/MKR/CLER LPS
- ← (002) 16 GRN (3) RH TURN LP
- ← (003) 16 YEL (4) LH TURN LP
- ← (004) 16 PNK (5) BACK-UP LPS
- ← (005) 16 RED (6) STOP LPS
- EMPTY (7)
- ← (090) 16 BLU/WHT (8) 3-WAY SW
- ← (091) 16 BLU/YEL (9) 3-WAY SW
- ← (800) 18 BLACK (10) RR DR GPS SW
- ← (007) 16 ORN (11) DOME LPS
- ← (554) 16 PNK (12) RR DR SOLENOID
- ← (051) 16 BLK/YEL (13) WORK LAMP 3WAY SW
- ← (052) 16 BLK/WHT (14) WORK LAMP 3WAY SW
- ← (050A) 16 BLK (15) WORK LAMP



AMP 1-480711-0  
CONN 15 CKT  
USE MALE TERMS

TO ROOF HARNESS



4"

BODY GROUND



4"

LH CLER LAMP



2"

LH ICC LAMP



2"

9" FROM



CONT'D FROM SHEET 1 OF 2

- (100) 18 WHT (1) GROUND
- (800) 18 BLK (2) RR DR GPS SW

AMP 172165-1  
CONN 2 CKT



4"



DEUTSCH DT04-2P

CONN 2 CKT

DEUTSCH 1060-16-0122 (G2)

TERMINALS

DEUTSCH W2P

WEDGE LOCK

- ← (004) 16 PNK (1) B/U SIGNAL
- ← (100) 16 WHT (2) GND



4"



10"

LH MKR LAMP

.180"F (100) 18 WHT MOLDED BLTT GROUND

.180"F (001) 18 BRN MOLDED BLTT LH MKR LP

VENDOR MAY SUBSTITUTE NON-INSULATED .180" F BULLET WITH HEAT SHRINK PER NOTE #9

.180"F (001) 16 BRN MOLDED BULLET LIC LP

.180"F (100) 18 WHT MOLDED BULLET GROUND

LICENSE LAMP

NOTE: RUN CIRCUIT 100 AS 16GA WHT FROM "C1" TO "T"  
ALL INSTANCES OF CKT 100 MUST BE ELECTRICALLY CONTINUOUS WITH CONNECTOR C1



12065172  
CONN 1 CKT  
FEMALE TERMS  
15324982  
SEAL  
12065249  
TPA

(554) 16 PNK RR DR SOLENOID



2"



4"

LH TURN/ TAIL LAMP (UPPER LP)



AMP 282087-1  
CONN 3 CKT

(100) 18 WHT (1) GROUND

(PLUG) EMPTY (2) (D2)

(003) 18 YEL (3) LH TURN LP

M/BODY TURN/MKR

.180"F (100) 18 WHT MOLDED BULLET GROUND

.180"F (001) 18 BRN MOLDED BULLET LH TAIL LP

.180"F (003) 18 YEL MOLDED BULLET LH TURN LP

.180"F (002) 18 GRN MOLDED BULLET RH TURN LP (A)



4"

LH STOP/ TAIL LAMP (LOWER LP)



AMP 282087-1  
CONN 3 CKT

(100) 18 WHT (1) GROUND

(001) 18 BRN (2) LH TAIL LP

(005) 18 RED (3) LH STOP LP

LH BACK-UP LAMP



AMP 282087-1  
CONN 3 CKT

(100) 18 WHT (1) GROUND

(PLUG) EMPTY (2)

(004) 18 PNK (3) LH BACK-UP LP

CONNECTOR


DELPHI 12010973

TERM

DELPHI 12089040

SEAL

DELPHI 15324982 (G1)



(F2)

(004) 18 PNK (A) B/U ALM

(100) 18 WHT (B) GROUND



(E3) (C)

**PROPRIETARY**  
This drawing and the information and data contained hereon constitutes valuable proprietary trade secret information of Morgan Olson and may not be used, duplicated or further disclosed or disseminated for any purpose other than that purpose for which it was originally provided, without the prior written consent of Morgan Olson.

**MORGAN OLSON**  
ANSI Y 14.5M-1994 REMOVE ALL SHARP EDGES

DO NOT SCALE DRAWING  
TOLERANCES:  
XXX ±.010  
XXX ±.020  
XXX ±.030  
XXX ±.040  
XXX ±.050  
XXX ±.060  
XXX ±.070  
XXX ±.080  
XXX ±.090  
XXX ±.100

DRAWN: EMM DATE: 6/4/19 ECO#: 59638  
DESCRIPTION: HARN RR P80 LED W/WRK LMP RUD GPS & M/BDY MKR  
PART#: 197086200 SHEET: 2 of 2 REV: L